

# LG 306

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>16X7.50 - 8</b>                       |
| <b>UM</b>           | US STANDARD                              |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                   |
| <b>MACHINERY</b>    | ÅKGRÄSKLIPPARE / LITEN TRAKTOR / TRAKTOR |
| <b>VERSION</b>      | ARAMID BELTED                            |
| <b>TIRE TYPE</b>    | TL                                       |



## DIMENSIONER US STANDARD

|                 |                              |            |                 |
|-----------------|------------------------------|------------|-----------------|
| <b>USA CODE</b> | 94062799                     | <b>ECE</b> | E11-106R-006731 |
| <b>SW (IN)</b>  | 7.0                          | <b>PR</b>  | 4               |
| <b>OD (IN)</b>  | 15.7                         |            |                 |
| <b>RIM REC</b>  | 5.375   - 55;   - 70;   - 90 |            |                 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>26</b> |
| 10               | 760       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.