


AGRIMAX V- FLECTO

TIRE SIZE	VF 540/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	154 D



DIMENSIONES US STANDARD

CÓDIGO USA	94062126	RC (IN)	163.8
SW (IN)	21.6	RIM REC	DW 20 B
OD (IN)	55.6	RIM ALT	DW 18 L
SLR (IN)	24.5	ECE	E11-106R-005710

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4210	4960	5630	6320	6910	7520
FROM 40 TO 25	4630	5460	6190	6940	7610	8270
20	4720	5560	6320	7080	7750	8430
12	4810	5670	6440	7220	7900	8600
5	5090	6000	6810	7640	8370	9090
*UPTO 5 CYC WITH FRONT LOADER	6480	7640	8660	9720	10650	11570
5 HT	4720	5560	6320	7080	7750	8430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.