


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/65 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	174 D



DIMENSIONI IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1913	RIM ALT	DW 21 B
SLR (MM)	852	ECE	E11-106R-005713
RC (MM)	5773	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3105	3590	4080	4630	5055	5485	6095
FROM 65 TO 40	3415	3950	4485	5090	5560	6030	6700
30	3480	4025	4570	5190	5670	6150	6830
20	3350	4105	4660	5290	5780	6270	6965
10	3755	4345	4930	5595	6115	6630	7370
*UPTO 10 CYC WITH FRONT LOADER	4780	5530	6275	7125	7780	8440	9380
10HT	3480	4025	4570	5190	5670	6150	6830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.