


AGRIMAX TERIS

| | |
|---------------------|--|
| TIRE SIZE | 620/75 R 26 CHO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CEIFEIRA / COLHEDORA DE ALGODÃO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 166 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 625 | RIM REC | DW 20 B |
| OD (MM) | 1590 | ECE | E4-106R-001419 |
| SLR (MM) | 730 | SRI | 750 |
| RC (MM) | 4851 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|
| 50 | 2440 | 2810 | 3445 | 3765 | 4135 | 4505 | 4880 | 5300 |
| 40 | 2440 | 2810 | 3445 | 3765 | 4135 | 4505 | 4880 | 5300 |
| 30 | 2615 | 3010 | 3690 | 4030 | 4430 | 4825 | 5225 | 5675 |
| 15 CYC | 4025 | 4635 | 5685 | 6210 | 6825 | 7435 | 8050 | 8745 |
| 10 CYC | 4390 | 5060 | 6205 | 6775 | 7445 | 8110 | 8780 | 9540 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.