DATA SHEET

PRINTED ON
21-04-2026

AS 504

TYRE SIZE	**10.0/75 - 15.3**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENTS
VERSION	INDUSTRIAL
TYRE TYPE	TL
LI/SS DRIVE WHEEL	106 A8
LI/SS FREE ROLLING	119 A8

DIMENSIONS US STANDARD

USA CODE	94019441	**RC (IN)**	94.6
SW (IN)	10.4	**RIM REC**	9.00
OD (IN)	30.9	**PR**	8
SLR (IN)	14.2		

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	45
5 FR	4200
15 FR	3570
20 FR	3360
25 FR	3000
5 DW	2930
15 DW	2490
20 DW	2350
25 DW	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..