


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 580/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 158 A8 |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 577 | RIM REC | W 18 L |
| OD (MM) | 1827 | RIM ALT | DW18L;DD18L |
| SLR (MM) | 823 | ECE | E11-106R-007608 |
| RC (MM) | 5456 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2135 | 2480 | 2830 | 3180 | 3530 | 3875 |
| 50 | 2240 | 2605 | 2975 | 3340 | 3705 | 4070 |
| 40 | 2335 | 2720 | 3100 | 2485 | 3865 | 4245 |
| 30 | 2455 | 2855 | 3260 | 3660 | 4060 | 4460 |
| 10 LT | 2860 | 3325 | 3795 | 4260 | 4730 | 5195 |
| 10 HT | 2455 | 2855 | 3260 | 3660 | 4060 | 4460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.