

RT 747 AGRO INDUSTRIAL

460/70 R 24

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ
VERSION	STANDARD
TIRE TYPE	TL
	152 A8/B



UNDEFINED IS STANDARD

SW (MM)	465	RIM REC	DW 15 L
OD (MM)	1254	RIM ALT	DW 14 L; DW 16 L
SLR (MM)	556	ECE	E11-106R-004071
RC (MM)	3840	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
50	1670	2060	2415	2805	3160	3550
40	1670	2060	2415	2805	3160	3550
30	1785	2205	2585	3000	3380	3800
25	1850	2285	2680	3115	3505	3940
10 CYC	2505	3090	3620	4205	4740	5325
STATIC	3505	4325	5070	5890	6635	7455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.