


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>180/95 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	105 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	185	<b>RIM REC</b>	5.5 F
<b>OD (MM)</b>	760	<b>RIM ALT</b>	6.0 F
<b>SLR (MM)</b>	340	<b>ECE</b>	E4-106R-000756
<b>RC (MM)</b>	2265	<b>SRI</b>	350

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	430	550	670	735	790	865	925	-
40	430	550	670	735	790	865	925	-
30	460	585	715	785	845	925	990	-
10	505	655	795	950	1085	1130	1255	1390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.