


# AGRIMAX V- FLECTO

|              |  |
|--------------|--|
| TIRE SIZE    | VF 650/85 R 42   |
| UM           | IS STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | TRACTOR DE ALTA POTENCIA /<br>TRACTOR  |
| VERSIÓN      | SPECIAL  |
| TIRE TYPE    | TL   |
| LI/SS        | 183 D  |



## DIMENSIONES IS STANDARD

|          |      |         |                  |
|----------|------|---------|------------------|
| SW (MM)  | 680  | RIM REC | DW 23 B          |
| OD (MM)  | 2160 | RIM ALT | DW20B;DW21B      |
| SLR (MM) | 938  | ECE     | E11-106R-0011307 |
| RC (MM)  | 6413 | SRI     | 1025             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4   | 1.6   | 2.0   |
|---------------|------|------|------|------|-------|-------|-------|
| 70            | 3980 | 4615 | 5250 | 5970 | 6605  | 7240  | 7960  |
| FROM 65 TO 40 | 4375 | 5075 | 5775 | 6560 | 7260  | 7960  | 8750  |
| 30            | 4460 | 5175 | 5890 | 6690 | 7405  | 8120  | 8925  |
| 20            | 4550 | 5275 | 6005 | 6825 | 7550  | 8280  | 9100  |
| 10            | 4810 | 5580 | 6350 | 7215 | 7985  | 8755  | 9625  |
| UPTO 30 CYC   | 4965 | 5755 | 6550 | 7445 | 8240  | 9035  | 9930  |
| UPTO 15 CYC   | 5925 | 6875 | 7820 | 8890 | 9835  | 10785 | 11855 |
| UPTO 10 CYC   | 6495 | 7530 | 8570 | 9740 | 10780 | 11820 | 12990 |
| 10HT          | 4460 | 5175 | 5890 | 6690 | 7405  | 8120  | 8925  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.