


# AGRIMAX RT 955

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>230/95 R 44</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PULVERIZADOR / VENDIMIADORA /<br>COSECHADORA / MAQUINARIA<br>AGRÍCOLA                    |
| <b>VERSIÓN</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 134 A8/B   |



## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 228  | <b>RIM REC</b> | W 7            |
| <b>OD (MM)</b>  | 1556 | <b>RIM ALT</b> | W 8            |
| <b>SLR (MM)</b> | 739  | <b>ECE</b>     | E4-106R-000777 |
| <b>RC (MM)</b>  | 4788 | <b>SRI</b>     | 750            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  | 4.4  |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50         | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | -    |
| 40         | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | -    |
| 30         | 890 | 1160 | 1410 | 1545 | 1635 | 1795 | 1955 | 2115 | 2270 | -    |
| 10         | 990 | 1245 | 1530 | 1815 | 2100 | 2165 | 2420 | 2675 | 2930 | 3180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.