


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 30 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 157 A8 ; 153 D |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94035816 | RC (IN) | 175.4 |
| SW (IN) | 17.4 | RIM REC | W 14 L |
| OD (IN) | 57.7 | RIM ALT | W 15 L |
| SLR (IN) | 26.3 | ECE | E4-106R-002297 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|------|------|------|------|------|------|
| 40 | 3780 | 4660 | 5470 | 6360 | 7160 | 8050 |
| 30 | 4020 | 4960 | 5820 | 6760 | 7620 | 8550 |
| 25 | 4280 | 5280 | 6180 | 7190 | 8090 | 9090 |
| 20 | 4450 | 5500 | 6450 | 7480 | 8430 | 9480 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.