

# RIB 774 (A)

<b>TIRE SIZE</b>	<b>18X8.50 - 8</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	85 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	225	<b>RIM REC</b>	7.00 I - 55 ; I - 70 ; I - 90
<b>OD (MM)</b>	460	<b>ECE</b>	E11-106R-004622
<b>SLR (MM)</b>	217	<b>PR</b>	6
<b>RC (MM)</b>	1390		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.00</b>
10 FR	720
25 FR	615
30 FR	575
40 FR	515

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.