

AGRIMAX RT 657

TIRE SIZE	480/65 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	142 D ; 145 A8



РАЗМЕРЫ US STANDARD

USA CODE	94028535	RC (IN)	161.1
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	52.6	RIM ALT	W 14 L
SLR (IN)	24.0	ECE	E4-106R-000653

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	2810	3270	3680	4090	4510	4850	5380	5840
30	2950	3440	3870	4300	4730	5100	5650	6140
25	3080	3580	4030	4480	4930	5310	5890	6390
20	3230	3770	4240	4710	5180	5590	6190	6720
5 LT	3770	4400	4940	5490	6040	6510	7220	7840
5 HT	3230	3770	4240	4710	5180	5590	6190	6720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.