

AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 230/95 R 44 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 134 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 228 | RIM REC | W 7 |
| OD (MM) | 1556 | RIM ALT | W 8 |
| SLR (MM) | 739 | ECE | E4-106R-000777 |
| RC (MM) | 4788 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50 | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | - |
| 40 | 830 | 1085 | 1315 | 1445 | 1530 | 1675 | 1825 | 1975 | 2120 | - |
| 30 | 890 | 1160 | 1410 | 1545 | 1635 | 1795 | 1955 | 2115 | 2270 | - |
| 10 | 990 | 1245 | 1530 | 1815 | 2100 | 2165 | 2420 | 2675 | 2930 | 3180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.