


AGRIMAX V- FLECTO

TIRE SIZE	VF 900/65 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STEEL BELTED SPL
TIRE TYPE	TL
LI/SS	193 D



DIMENSIONES IS STANDARD

SW (MM)	900	RIM REC	DW 30B
OD (MM)	2338	ECE	E11-106R-0010524
SLR (MM)	1006	SRI	1100
RC (MM)	7003		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	5335	6170	7010	7950	8685	9415	10465
FROM 65 TO 40	5865	6785	7705	8740	9545	10350	11500
30	5980	6920	7855	8910	9735	10555	11730
20	6095	7055	8010	9085	9925	10760	11960
10	6450	7460	8475	9610	10495	11385	12650
UPTO 30 CYC	6655	7695	8740	9915	10830	11745	13050
UPTO 15 CYC	7945	9190	10435	11840	12930	14020	15580
UPTO 10 CYC	8705	10070	11440	12975	14170	15365	17075
10HT	5980	6920	7855	8910	9735	10555	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.