


# AGRIMAX RT 955

	<b>210/95 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / ÜZÜM HASAT MAKİNESİ / BIÇERDÖVER / UYGULAMALI MAKİNE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	120 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94040018	<b>RC (IN)</b>	145.8
<b>SW (IN)</b>	8.4	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	47.8	<b>RIM ALT</b>	W 6
<b>SLR (IN)</b>	22.5	<b>ECE</b>	E4-106R-001391

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52
30	1420	1830	2230	2410	2620	2880	3090	-
25	1420	1830	2230	2410	2620	2880	3090	-
20	1520	1950	2380	2580	2810	3080	3310	-
5	2000	2600	3150	3430	3660	4030	4350	4630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.