


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 710/75 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	183 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94066339	<b>RC (IN)</b>	242.2
<b>SW (IN)</b>	28.3	<b>RIM REC</b>	DW 24 B
<b>OD (IN)</b>	81.1	<b>RIM ALT</b>	DW 23 B; DW 25 B
<b>SLR (IN)</b>	35.6	<b>ECE</b>	E11-106R-006764

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	8770	10170	11580	13150	14560	15960	17550
<b>FROM 40 TO 25</b>	9640	11190	12730	14460	16000	17550	19290
20	9830	11410	12980	14750	16320	17890	19680
12	10030	11630	13240	15030	16640	18240	20060
5	10600	12300	14000	15910	17600	19300	21220
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	13500	15660	17820	20240	22400	24560	27010
5 HT	9830	11410	12980	14750	16320	17890	19680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.