

# PL 801

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>6.00 - 9</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | ADAINEUR ROTATIF / MOISSONNEUSE<br>/ CHARIOT ÉLEVATEUR /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / CHARIOT ÉLEVATEUR |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 114 A8   |



## DIMENSIONS IS STANDARD

|                |                 |           |    |
|----------------|-----------------|-----------|----|
| <b>SW (MM)</b> | 157             | <b>PR</b> | 10 |
| <b>OD (MM)</b> | 543             |           |    |
| <b>RIM REC</b> | 4.00 E          |           |    |
| <b>ECE</b>     | E11-106R-003564 |           |    |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b>         | <b>8.50</b> |
|---------------------------|-------------|
| <b>25 LOAD WHEEL</b>      | 1715        |
| <b>25 STEER WHEEL</b>     | 1320        |
| <b>10 OTHER VEHICLES</b>  | 1715        |
| <b>25 OTHER VEHICLES</b>  | 1320        |
| <b>STATIC SIDE LOADER</b> | 1995        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.