

AGRIMAX V-FLECTO

TYRE SIZE	VF 650/60 R 38 NRO
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	173 D



DIMENSIONS US STANDARD

USA CODE	94065370	RC (IN)	205.4
SW (IN)	25.6	RIM REC	DW 23 B
OD (IN)	68.7	RIM ALT	DW 21 B
SLR (IN)	30.5	ECE	E11-106R-006415

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6010	6910	7960	8870	9920	10820	12140	13040
FROM 40 TO 25	6590	7590	8740	9740	10890	11890	13330	14330
20	6720	7750	8920	9940	11110	12140	13600	14620
12	6860	7900	9090	10140	11330	12380	13870	14900
5	7250	8360	9620	10720	11980	13080	14660	15760
*UPTO 5 CYC WITH FRONT LOADER	9240	10640	12250	13650	15260	16650	18660	20060
5 HT	6720	7750	8920	9940	11110	12140	13600	14620

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.