


AGRIMAX FORCE



TYRE SIZE	IF 710/60 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	168 D

DIMENSIONS US STANDARD

USA CODE	94038541	RC (IN)	189.5
SW (IN)	27.9	RIM REC	DW 25 B
OD (IN)	63.5	ECE	E4-106R-001407
SLR (IN)	28.1	TRA CODE	R1W

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5160	5940	6840	7630	8530	9310	10440	11230
FROM 40 TO 25	5680	6540	7530	8390	9380	10240	11470	12300
20	5900	6790	7830	8720	9750	10650	11930	12830
12	6130	7050	8120	9050	10130	11060	12390	13330
5	7210	8300	9560	10650	11900	13000	14570	15670
UPTO 20 CYC	7370	8490	9780	10900	12190	13300	14910	16050
UPTO 10 CYC	8800	10130	11660	13000	14540	15860	17780	19140
UPTO 5 CYC	9640	11110	12800	14250	15940	17400	19500	20990
5 HT	5900	6790	7830	8720	9750	10650	11930	12830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.