


AGRIMAX V-FLECTO



TIRE SIZE	VF 600/60 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	157 D

РАЗМЕРЫ US STANDARD

USA CODE	94058495	RC (IN)	166.5
SW (IN)	23.1	RIM REC	DW 20 B
OD (IN)	56.7	RIM ALT	DW 18 L
SLR (IN)	24.9	ECE	E11-106R-004471

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4540	5290	6030	6780	7520	8270
FROM 40 TO 25	4990	5820	6640	7450	8270	9095
20	5090	5930	6770	7590	8430	9270
12	5190	6050	6900	7750	8600	9460
5	5490	6390	7300	8190	9090	10000
*UPTO 5 CYC WITH FRONT LOADER	6990	8150	9280	10430	11570	12730
5 HT	5090	5930	6770	7590	8430	9270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.