


AGRIMAX V-FLECTO

TIRE SIZE	VF 520/60 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	149 D



DIMENSIONS IS STANDARD

SW (MM)	516	RIM REC	DW 18 L
OD (MM)	1335	RIM ALT	W 18 L
SLR (MM)	587	ECE	E11-106R-005497
RC (MM)	3910	SRI	650

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	1620	1890	2155	2425	2685	2955
FROM 65 TO 40	1785	2080	2370	2665	2955	3250
30	1820	2120	2415	2715	3010	3315
20	1855	2160	2460	2770	3070	3380
10	1960	2285	2605	2930	3250	3575
*UPTO 10 CYC WITH FRONT LOADER	2495	2910	3315	3730	4135	4550
10HT	1820	2120	2415	2715	3010	3315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.