

TR 678

| | |
|---------------------|---|
| TIRE SIZE | 600/65 - 34 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПОГРУЗОЧНО- ТРАНСПОРТНАЯ МАШИНА / ЭКСКАВАТОР / ПРИЦЕП |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 164 A2 ; 160 A6 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|-----------------|-----------------|
| SW (MM) | 610 | RIM REC | DW 20 B |
| OD (MM) | 1644 | ECE | E11-106R-003648 |
| SLR (MM) | 758 | PR | 14 |
| RC (MM) | 4916 | TRA CODE | LS2 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.40 |
|------------|------|
| 30 | 4500 |
| 10 | 5000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.