


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>400/80 R 28 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	151 A8 ; 146 D



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	404	<b>RIM REC</b>	W 13
<b>OD (MM)</b>	1352	<b>RIM ALT</b>	W 12 ; W 14 L
<b>SLR (MM)</b>	615	<b>ECE</b>	E4-106R-002401
<b>RC (MM)</b>	4048	<b>SRI</b>	650

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.6	2.0	2.4	2.8	3.2
65	1410	1740	2040	2370	2670	3000
50	1530	1890	2215	2575	2900	3260
40	1620	2000	2345	2725	3070	3450
30	1690	2090	2450	2845	3205	3600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.