

AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 D ; 158 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1542 | RIM ALT | W 18 L |
| SLR (MM) | 697 | ECE | E4-106R-001825 |
| RC (MM) | 4609 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 1860 | 2170 | 2445 | 2715 | 2985 | 3220 | 3565 | 3875 |
| 50 | 1955 | 2280 | 2565 | 2850 | 3135 | 3380 | 3745 | 4070 |
| 40 | 2040 | 2380 | 2680 | 2975 | 3275 | 3530 | 3910 | 4250 |
| 30 | 2145 | 2500 | 2810 | 3125 | 3435 | 3705 | 4105 | 4460 |
| 10 LT | 2495 | 2910 | 3275 | 3640 | 4005 | 4315 | 4780 | 5195 |
| 10 HT | 2145 | 2500 | 2810 | 3125 | 3435 | 3705 | 4105 | 4460 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.