


RIDEMAX FROST

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 28 IND |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 156 A8 ; 151 D |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94513338 | RC (IN) | 169.1 |
| SW (IN) | 17.4 | RIM REC | DW 14 L |
| OD (IN) | 55.9 | RIM ALT | DW 15 L |
| SLR (IN) | 25.3 | ECE | E11-106R-0010949 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 38 | 41 | 44 | 46 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 45 | 3350 | 4420 | 5320 | 5860 | 6240 | 6550 | 6840 | 7230 | 7610 |
| 30 | 3630 | 4770 | 5760 | 6340 | 6750 | 7080 | 7410 | 7810 | 8220 |
| 25 | 3880 | 5110 | 6170 | 6790 | 7230 | 7580 | 7940 | 8380 | 8820 |
| 20 | 4020 | 5300 | 6390 | 7030 | 7480 | 7860 | 8220 | 8670 | 9130 |
| 10 | 4220 | 5570 | 6710 | 7390 | 7870 | 8260 | 8630 | 9120 | 9590 |
| 5 | 4830 | 6360 | 7670 | 8440 | 8990 | 9420 | 9870 | 10420 | 10960 |
| 3 | 5600 | 7370 | 8910 | 9790 | 10430 | 10930 | 11440 | 12080 | 12710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.