

# LG 306

|                     |                                     |
|---------------------|-------------------------------------|
| <b>TIRE SIZE</b>    | 23X10.5 - 12                        |
| <b>UM</b>           | US STANDARD                         |
| <b>CONSTRUCTION</b> | BIAS                                |
| <b>MACHINERY</b>    | RASENMÄHER / KLEINTRAKTOR / TRACTOR |
| <b>VERSION</b>      | ARAMID BELTED                       |
| <b>TIRE TYPE</b>    | TL                                  |



## ABMESSUNGEN US STANDARD

|                 |          |                |                             |
|-----------------|----------|----------------|-----------------------------|
| <b>USA-CODE</b> | 94012800 | <b>RC (IN)</b> | 66.8                        |
| <b>SW (IN)</b>  | 10.2     | <b>RIM REC</b> | 8.5 I - 55                  |
| <b>OD (IN)</b>  | 23.0     | <b>RIM ALT</b> | 7.00 I - 55; I - 70; I - 90 |
| <b>SLR (IN)</b> | 10.3     | <b>ECE</b>     | E11-106R-003580             |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>32</b> |
| 10               | 1760      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.