


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 480/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94512331	<b>RC (IN)</b>	186.6
<b>SW (IN)</b>	19.5	<b>RIM REC</b>	W 18 L
<b>OD (IN)</b>	62.2	<b>RIM ALT</b>	W 16 L; DW 18 L
<b>SLR (IN)</b>	27.9	<b>ECE</b>	E11-106R-0010578

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	4140	4890	5630	6270	7020	7660	8400	9040	9890	10630
<b>FROM 40 TO 25</b>	4560	5380	6190	6900	7720	8420	9240	9930	10870	11680
20	4650	5490	6320	7030	7870	8590	9410	10130	11090	11920
12	4740	5590	6450	7180	8020	8750	9600	10330	11300	12150
5	5020	5920	6810	7580	8490	9260	10160	10930	11960	12850
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	6380	7530	8670	9660	10800	11780	12930	13910	15220	16360
5 HT	4650	5490	6320	7030	7870	8590	9410	10130	11090	11920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.