

AW 702

| | |
|---------------------------|---|
| TIRE SIZE | 10.5/65 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI / RIMORCHIO |
| VERSIONE | STANDARD |
| TIRE TYPE | TT |
| LI/SS FREE ROLLING | 123 A8 |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 270 | RIM REC | W 9 |
| OD (MM) | 760 | RIM ALT | W 8; W 8 L |
| SLR (MM) | 350 | ECE | E11-106R-003513 |
| RC (MM) | 2329 | PR | 10 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.80 |
|-------------------|-------------|
| 10 FR | 2170 |
| 25 FR | 1845 |
| 30 FR | 1735 |
| 40 FR | 1550 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.