

FLOTATION 558

| | |
|---------------------------|--------------------------------------|
| TYRE SIZE | 400/55 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | HAY HARVESTER / TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 138 A8/134 B |
| LI/SS FREE ROLLING | 150 A8/146 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------|
| USA CODE | 94006243 | RC (IN) | 121.4 |
| SW (IN) | 15.9 | RIM REC | AG 11.75 |
| OD (IN) | 40.2 | RIM ALT | 12.25; 13.00; AG 13.00 |
| SLR (IN) | 17.5 | ECE | E4-106R-002261 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 44 | 46 | 51 |
|-----------|------|------|-------|
| 5 FR | 9450 | 9810 | 10340 |
| 10 FR | 8500 | 8830 | 9300 |
| 20 FR | 7550 | 7850 | 8270 |
| 25 FR | 6750 | 7010 | 7390 |
| 30 FR | 6070 | 6300 | 6610 |
| 5 DW | 6650 | 6910 | 7290 |
| 10 DW | 5990 | 6220 | 6560 |
| 20 DW | 5320 | 5530 | 5830 |
| 25 DW | 4750 | 4940 | 5200 |
| 30 DW | 4280 | 4440 | 4670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.