


# AGRIMAX RT 657

<b>TYRE SIZE</b>	<b>600/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	154 D ; 157 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1491	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	670	<b>ECE</b>	E4-106R-000621
<b>RC (MM)</b>	4470	<b>SRI</b>	700

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1800	2100	2365	2625	2890	3115	3450	3750
<b>50</b>	1895	2210	2485	2760	3035	3275	3625	3940
<b>40</b>	1980	2310	2600	2890	3180	3425	3795	4125
<b>30</b>	2075	2420	2720	3025	3325	3585	3970	4315
<b>10 LT</b>	2415	2815	3170	3520	3870	4175	4625	5025
<b>10 HT</b>	2075	2420	2720	3025	3325	3585	3970	4315

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.