


# AGRIMAX TURF RT 333

<b>TIRE SIZE</b>	<b>420/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	137 A8 ; 137 B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	435	<b>RIM REC</b>	W 15 L
<b>OD (MM)</b>	1324	<b>RIM ALT</b>	DW15L;DW14L
<b>SLR (MM)</b>	594	<b>ECE</b>	E11-106R-0010344
<b>RC (MM)</b>	3957	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	1265	1475	1680	1890	2095	2300
40	1265	1475	1680	1890	2095	2300
30	1360	1580	1800	2025	2245	2465
10 LT	1700	1975	2255	2530	2810	3085
10 HT	1360	1580	1800	2025	2245	2465

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.