


AGRIMAX FORTIS

| | |
|--------------|--|
| TIRE SIZE | 600/70 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 158 D ; 161 A8 |



DIMENSIONS IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1602 | RIM ALT | DW 18 L; W 18 L |
| SLR (MM) | 724 | ECE | E4-106R-001400 |
| RC (MM) | 4810 | SRI | 750 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 2040 | 2380 | 2680 | 2975 | 3275 | 3530 | 3910 | 4250 |
| 50 | 2145 | 2505 | 2815 | 3130 | 3440 | 3710 | 4110 | 4465 |
| 40 | 2220 | 2590 | 2915 | 3240 | 3565 | 3840 | 4255 | 4625 |
| 30 | 2350 | 2740 | 3085 | 3425 | 3770 | 4060 | 4500 | 4890 |
| 10 LT | 2735 | 3190 | 3590 | 3990 | 4390 | 4730 | 5240 | 5695 |
| 10 HT | 2350 | 2740 | 3085 | 3425 | 3770 | 4060 | 4500 | 4890 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.