


FL 635

TIRE SIZE	650/55 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	167 D



DIMENSÕES US STANDARD

CÓDIGO USA	94043521	RC (IN)	153.6
SW (IN)	25.4	RIM REC	AG 20.00
OD (IN)	50.7	ECE	E4-106R-000803
SLR (IN)	22.4		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	3510	4000	4490	5580	6350	7330	8310	9080	9950	10930
40	3850	4390	4930	6130	6980	8060	9140	9980	10930	12010
30	4660	5310	5960	7420	8440	9740	11060	12070	13240	14540
25	5240	5970	6710	8340	9490	10960	12430	13570	14880	16350
15	6080	6940	7790	9690	11020	12730	14440	15770	17280	18990
5	6920	7900	8870	11030	12540	14490	16450	17960	19690	21630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.