

LOADER SPECIAL



LOADER SPECIAL



LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	29.5 - 25	TL	L5	32	-	25.00/3.5	-	0	770	1930	884	5753	99,5	STD
	26.5 - 25	TL	L5	28	-	22.00/3.0	-	0	686	1815	833	5372	93,5	STD
	20.5 - 25	TL	L5	20	-	17.00/2.0	-	0	530	1570			85	STD
	29.5 - 25	TL	L5	28	-	25.00/3.5	-	0	770	1930	884	5753	99,5	STD
	26.5 - 25	TL	L5	32	-	22.00/3.0	-	0	686	1815	833	5372	93,5	STD

STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES			PERFORMANCES		
					
					
-	-				

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø33"	35/65 - 33	TL	L5	42	-	28.00/3.5	-	0	910	2105	976	6505	99,5	STD
Ø39"	40/65 - 39	TL	L5	56	-	32.00/4.0	-	0	1000	2405	0	0	108	SB
Ø45"	45/65 - 45	TL	L5	58	-	36.00/4.5	-	0	1185	2785	0	0	116	SB

STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
-	-	Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index	