

## RT 857

|                     |                                                                                          |
|---------------------|------------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>420/85 R 28</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                              |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR                                                                                  |
| <b>VERSION</b>      | STANDARD                                                                                 |
| <b>TIRE TYPE</b>    | TL                                                                                       |
| <b>LI/SS</b>        | 139 A8/B                                                                                 |



### DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 450  | <b>RIM REC</b> | W 15 L         |
| <b>OD (MM)</b>  | 1425 | <b>RIM ALT</b> | W 14 L ; W 13  |
| <b>SLR (MM)</b> | 640  | <b>ECE</b>     | E4-106R-000770 |
| <b>RC (MM)</b>  | 4276 | <b>SRI</b>     | 675            |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|--------------|------|------|------|------|------|------|
| <b>50</b>    | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| <b>40</b>    | 1340 | 1560 | 1775 | 1995 | 2215 | 2430 |
| <b>30</b>    | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |
| <b>10 LT</b> | 1795 | 2090 | 2380 | 2675 | 2970 | 3260 |
| <b>10 HT</b> | 1435 | 1670 | 1905 | 2140 | 2375 | 2605 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.