


# AGRIMAX RT 657

TIRE SIZE	540/65 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	146 D ; 149 A8



## BOYUTLAR US STANDARD

USA CODE	94066636	RC (IN)	154.7
SW (IN)	20.9	RIM REC	W 16 L
OD (IN)	51.7	RIM ALT	W 18 L
SLR (IN)	23.2	ECE	E4-106R-000773

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3170	3700	4170	4630	5090	5490	6080	6600
30	3340	3890	4380	4860	5360	5760	6390	6940
25	3440	4010	4520	5020	5520	5950	6590	7160
20	3660	4270	4790	5320	5860	6320	7000	7610
5 LT	4250	4970	5590	6210	6830	7360	8160	8860
5 HT	3660	4270	4790	5320	5860	6320	7000	7610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.