

# TR 117

|                     |                                       |
|---------------------|---------------------------------------|
| <b>TIRE SIZE</b>    | <b>11.2 - 24</b>                      |
| <b>UM</b>           | US STANDARD                           |
| <b>CONSTRUCTION</b> | ⊠ BIAS                                |
| <b>MACHINERY</b>    | ARROSEUR À PIVOT / OUTILLAGE AGRICOLE |
| <b>VERSION</b>      | STANDARD                              |
| <b>TIRE TYPE</b>    | TT                                    |
| <b>LI/SS</b>        | 106 A8                                |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94028368 | <b>RC (IN)</b> | 126.2          |
| <b>SW (IN)</b>  | 11.2     | <b>RIM REC</b> | W 10           |
| <b>OD (IN)</b>  | 42.9     | <b>RIM ALT</b> | W 9            |
| <b>SLR (IN)</b> | 20.0     | <b>ECE</b>     | E4-106R-001967 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 26   | 34   |
|--------------|------|------|
| 25           | 2090 | ---  |
| <b>CREEP</b> | ---  | 4420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.