

GR 288



GR 288

GR 288 (G-2/L-2) is a versatile bias-ply tyre for graders or loaders. It is ideal for use in construction, site preparation, road building, and other soft or muddy environments. The self-cleaning tread pattern provides excellent traction, and you can expect a long tyre life as a result of the special cut-and-chip-resistant compound.



	SIZE	TT/TL	PR	LI/SS	RIM		OW (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	VERSION
					REC RIM	ALT RIM						
												
Ø25"	17.5 - 25	TL	16	-	14.00/1.5	14.00/1.3 (DC)	445	1330	596	3950	25,5	STD
	17.5 - 25	TL	12	-	14.00/1.5	14.00/1.5 (DC) 14.00/1.3 (DC)	445	1330	596	3950	25,5	STD
	15.5 - 25	TL	12	-	12.00/1.3	12.00/1.3 (DC)	385	1270	572	3772	24	STD
	20.5 - 25	TL	16	-	17.00/2.0	17.00/1.7	520	1480	656	4396	28,5	STD

STD: STANDARD, DB HD: DUAL BEAD HD

TECHNOLOGIES		PERFORMANCES	
	 G2/L2		
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	PR	LI/SS	RIM		OW (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	VERSION
				REC RIM	ALT RIM						
											
23.5 - 25	TL	16	-	19.50/2.5	-	595	1610	708	4782	30,5	STD
20.5 - 25	TL	20	-	17.00/2.0	17.00/1.7	520	1480	656	4396	28,5	STD
17.5 - 25	TT	20	-	14.00/1.5	14.00/1.3 (DC)	445	1330	596	3950	25,5	DB HD
23.5 - 25	TL	20	-	19.50/2.5	-	595	1610	708	4782	30,5	STD

STD: STANDARD, DB HD: DUAL BEAD HD



TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026