


AGRIMAX V-FLECTO



TIRE SIZE	VF 710/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STEEL BELTED
TIRE TYPE	TL
LI/SS	193 D

ABMESSUNGEN IS STANDARD

SW (MM)	720	RIM REC	DW 25 B
OD (MM)	2058	RIM ALT	DW 23 B; DW 24 B
SLR (MM)	928	ECE	E11-106R-0010960
RC (MM)	6233	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
70	3875	4500	5130	5865	6490	7120	7850	8270	9105	9840	10465
FROM 65 TO 40	4255	4945	5635	6440	7130	7820	8625	9085	10005	10810	11500
30	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030	11730
20	4430	5145	5865	6700	7420	8135	8970	9450	10410	11245	11960
10	4685	5440	6200	7085	8745	8605	9490	9995	11010	11895	12650
*UPTO 10 CYC WITH FRONT LOADER	5960	6925	7890	9020	9985	10950	12075	12720	14010	15135	16100
10 HT	4345	5045	5750	6570	7275	7980	8800	9270	10210	11030	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.