

FLOTATION 648

| | |
|---------------------------|---------------------------------------------------------------------------------------|
| TIRE SIZE | 600/55 - 26.5 |
| UM | IS STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 153 A8/149 B |
| LI/SS FREE ROLLING | 165 A8/161 B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | AG 20.00 |
| OD (MM) | 1354 | ECE | E4-106R-002277 |
| SLR (MM) | 581 | PR | 12 |
| RC (MM) | 4017 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.50 | 1.80 | 2.00 |
|------------|------|------|------|
| 10 FR | 6090 | 6775 | 7210 |
| 20 FR | 5480 | 6100 | 6490 |
| 30 FR | 4870 | 5420 | 5770 |
| 40 FR | 4350 | 4840 | 5150 |
| 50 FR | 3915 | 4355 | 4625 |
| 10 DW | 4320 | 4800 | 5110 |
| 20 DW | 3885 | 4320 | 4600 |
| 30 DW | 3455 | 3840 | 4090 |
| 40 DW | 3085 | 3430 | 3650 |
| 50 DW | 2775 | 3085 | 3250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.