


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 480/80 R 50 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STEEL BELTED SPL |
| TIRE TYPE | TL |

DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA CODE | 94512225 | RC (IN) | 243.9 |
| SW (IN) | 18.9 | RIM REC | DW16L |
| OD (IN) | 80.2 | RIM ALT | DW15L |
| SLR (IN) | 36.9 | ECE | E11-106R-0010595 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------------------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5750 | 6690 | 7620 | 8710 | 9640 | 10570 | 11660 | 12280 | 13520 | 14620 | 15540 |
| FROM 40 TO 25 | 6330 | 7350 | 8380 | 9570 | 10590 | 11620 | 12820 | 13500 | 14870 | 16060 | 17080 |
| 20 | 6450 | 7500 | 8540 | 9770 | 10810 | 11860 | 13070 | 13770 | 15170 | 16390 | 17430 |
| 12 | 6580 | 7650 | 8710 | 9950 | 11020 | 12090 | 13330 | 14040 | 15460 | 16710 | 17770 |
| 5 | 6960 | 8090 | 9210 | 10530 | 11660 | 12790 | 14100 | 14850 | 16360 | 17670 | 18790 |
| UPTO 20 CYCLIC | 7180 | 8340 | 9500 | 10870 | 12030 | 13190 | 14550 | 15320 | 16880 | 18230 | 19390 |
| UPTO 10 CYCLIC | 8560 | 9950 | 11340 | 12960 | 14350 | 15740 | 17360 | 18290 | 20140 | 21760 | 23150 |
| UPTO 5 CYCLIC | 9390 | 10910 | 12430 | 14210 | 15730 | 17250 | 19020 | 20040 | 22070 | 23840 | 25360 |
| 5 HT | 6450 | 7500 | 8540 | 9770 | 10810 | 11860 | 13070 | 13770 | 15170 | 16390 | 17430 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.