

AGRIMAX RT 855

TIRE SIZE	520/85 R 46
UM	US STANDARD
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	158 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94062072	RIM ALT	DW 18 L ; W 18 L ; W 18 A
SW (IN)	20.3	ECE	E4-106R-001415
OD (IN)	80.8	TRA CODE	R1W
SLR (IN)	36.6	TREAD DEPTH (32nd)	71.19
RC (IN)	242.4	TMPH (TM/H)	1
RIM REC	DW 16 L ; W 16 A ; W 16 L ; DD 16		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	5160	6000	6840	7680	8530	9370
25	5160	6000	6840	7680	8530	9370
20	5520	6430	7330	8230	9140	10030
5 LT	6910	8040	9170	10300	11430	12550
5 HT	5520	6430	7330	8230	9140	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.