

# AW 702

<b>TIRE SIZE</b>	<b>10.0/80 - 12</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / OUTILLAGE AGRICOLE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE
<b>VERSION</b>	ARAMID BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	121 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	264	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	710	<b>RIM ALT</b>	7.0
<b>SLR (MM)</b>	317	<b>ECE</b>	E11-106R-003576
<b>RC (MM)</b>	2144	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.90</b>
<b>10 FR</b>	2030
<b>25 FR</b>	1725
<b>30 FR</b>	1625
<b>40 FR</b>	1450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.