


FL 639

TIRE SIZE	560/45 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE ÎMPRĂȘTIAT / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 D ; 163 A8



DIMENSIUNI IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1076	ECE	E4-106R-000627
SLR (MM)	484	SRI	525
RC (MM)	3303		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1040	1200	1360	1620	1910	2170	2430	2720	2980	3235
65	1140	1320	1495	1790	2095	2380	2700	2960	3270	3550
50	1380	1595	1810	2150	2540	2900	3240	3615	3960	4300
40	1560	1805	2050	2450	2880	3270	3675	4090	4485	4875
25	1800	2080	2360	2820	3310	3775	4230	4700	5165	5610
10	2045	2365	2685	3200	3775	4300	4820	5350	5880	6390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.