


AGRIMAX RT 855

TIRE SIZE	280/85 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	122 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94072927	RC (IN)	117.2
SW (IN)	11.5	RIM REC	W 10
OD (IN)	38.7	RIM ALT	W 9
SLR (IN)	17.6	ECE	E11-106R-007936

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1360	1590	1820	2050	2280	2480	2940	3310
25	1360	1590	1820	2050	2280	2480	2940	3310
20	1450	1710	1950	2200	2450	2660	3150	3540
5 LT	1820	2130	2450	2760	3060	3330	3950	4430
5 HT	1450	1710	1950	2200	2450	2660	3150	3540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.