DATA SHEET

PRINTED ON
23-04-2026

AT 603

	12.5/80 - 18
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	UYGULAMALI MAKINE / BEKOLODER / UYGULAMALI MAKINE / BEKOLODER
VERSION	STANDARD
TIRE TYPE	TL
	138 A8
	150 A8

UNDEFINED IS STANDARD

SW (MM)	308	**RIM REC**	W 9
OD (MM)	1000	**RIM ALT**	11
SLR (MM)	448	**ECE**	E11-106R-004352
RC (MM)	3027	**PR**	18

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.50
10 FR	4690
25 FR	3985
30 FR	3750
40 FR	3350
10 DW	3305
25 DW	2810
30 DW	2645
40 DW	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..