


AGRIMAX FORCE

TIRE SIZE	IF 710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	179 D



DIMENSIONER US STANDARD

USA CODE	94040926	RC (IN)	242.8
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	81.1	RIM ALT	DW 23 B
SLR (IN)	36.2	ECE	E4-106R-001830

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7300	8390	9630	10880	12120	13370	14600	15540
FROM 40 TO 25	8020	9230	10590	11960	13330	14690	16060	17100
20	8340	9590	11010	12430	13860	15280	16700	17770
12	8660	9950	11430	12910	14380	15860	17340	18450
5	10180	11710	13450	15180	16920	18650	20390	21690
UPTO 20 CYC	10430	11990	13770	15540	17320	19090	20880	22210
UPTO 10 CYC	12430	14300	16410	18530	20650	22770	24890	26480
UPTO 5 CYC	13630	15670	18000	20330	22650	24980	27290	29040
5 HT	8340	9590	11010	12430	13860	15280	16700	17770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.