


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 650/75 R 32 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ERNTemaschine / STREUMaschine / TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 172 A8/B |



ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA-CODE | 94055968 | RC (IN) | 213.2 |
| SW (IN) | 25.8 | RIM REC | DW 21 B |
| OD (IN) | 70.4 | RIM ALT | DW 20 B; DW 23 B |
| SLR (IN) | 31.8 | ECE | E11-106R-004755 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 6390 | 7360 | 9030 | 9870 | 10840 | 11810 | 12790 | 13890 | - | - |
| 25 | 6390 | 7360 | 9030 | 9870 | 10840 | 11810 | 12790 | 13890 | - | - |
| 20 | 6840 | 7880 | 9670 | 10560 | 11610 | 12640 | 13690 | 14870 | - | - |
| 5 LT | 8560 | 9880 | 12100 | 13230 | 14530 | 15830 | 17130 | 18620 | - | - |
| 5 HT | 6840 | 7880 | 9670 | 10560 | 11610 | 12640 | 13690 | 14870 | - | - |
| 5 CYC. | - | 10520 | 13460 | 14760 | 17120 | 18770 | 20550 | 22320 | 22670 | 23610 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.