


# AS 504

<b>TIRE SIZE</b>	<b>15.0/55 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELEHANDLER / FIELD TRAILER / IMPLEMENTS / TELEHANDLER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	122 A8
<b>LI/SS FREE ROLLING</b>	134 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94018833	<b>RC (IN)</b>	102.7
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	35.0	<b>RIM ALT</b>	13
<b>SLR (IN)</b>	15.6	<b>ECE</b>	E4-106R-001571

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	38
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.